

Fiber Optic Closure

Dome Closure - DOFC Series

AJW DOFC series is designed to manage large capacity of fiber splices with ease of maintenance for installers. It is suited for direct buried, underground and aerial applications. It offers simple re-entry system with O-ring clamp mechanism and does not require an electric hand tool.



DOFC-C3



DOFC-D1



DOFC-D2

Specifications

Model No.	Dimension(mm) Ø x H	Weight	Cable Port	Splice Tray	Fiber Splice	IP
DOFC-C3	Ø160 x 510 (Base: Ø146, Clamp: L225)	2.2kg	Round Port: 4 (Ø21) Oval Port: 1 (31.4 x 61)	6	144 fs	68
DOFC-C4	Ø160 x 510 (Base: Ø146, Clamp: L225)	2.3kg	Round Port: 7 (2: Ø20.7, 5: Ø18.7) Oval Port: 1 (31.4 x 61)	6	144 fs	68
DOFC-D1	Ø199.5 x 585 (Base: Ø181, Clamp: L260)	3.4kg	Round Port: 6 (4: Ø27, 2: Ø19) Oval Port: 1 (38 x 68.5)	9 (7+2)	300 fs (252 fs+48 fs)	68
DOFC-D2	Ø242 x 655 (Base: Ø238, Clamp: L295)	6.0kg	Round Port: 6 (Ø31.5) Oval Port: 1 (45 x 75)	10 (9+1)	672 fs (648 fs+24 fs)	68

All components are compliant with EU RoHS Directive (2011/65/EU amended by 2015/863).